


## NON-RETURN VALVES



### 184SC

## CAST IRON SWING PATTERN NON-RETURN VALVE



### Part No. 184SC

### CAST IRON BODY WITH FLANGE CONNECTIONS

SIZE	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250	DN300
A	200	203	216	241	292	330	356	495	622	698
B	150	165	185	200	220	250	285	340	405	460
C	98	114	127	134	153	165	184	273	324	337

This cast iron bolted bonnet swing check valves is robustly constructed and is ideally suited for a water and oil applications.

It can be fitted in the horizontal position or in the vertical position with the flow going upwards.

#### Features & Benefits

- Specifications to BS 5153.
- Bronze trim.
- Bolted bonnet.

#### Pressure & Temperature

PN16 Rated

For the working pressures and temperatures, see the flange rating table in the technical data section.

#### MATERIALS

Body	Cast Iron
Disc & Seat	Bronze
Bonnet	Cast Iron

#### Other Options Available

Outside lever & weight  
Rubber faced (Maximum temperature 65°C)

**THIS PRODUCT IS HELD IN STOCK WITH FLANGES UNDRILLED TO  
ENABLE US TO DRILL TO YOUR REQUIREMENTS**