


KENT (ELSTER) OIL METERS



FA

**FLANGED
OIL METER**



Part No. FA

CAST IRON BODY WITH PN16 FLANGED CONNECTIONS

The Kent FA flanged oil meters provide an accurate, reliable and economical way of obtaining all the information a user needs to control oil usage and energy costs. The meters handle a wide range of viscosity's, for a variety of applications including checking and totalising fuel for burners, furnaces and diesel engines, recording draw off from storage tanks and recording general usage.

These meters are also available with a volt-free pulser incorporated within the register.

SIZE	A	B	C*	C* WITH PULSER
FA15	165	95	180	210
FA20	165	105	210	220
FA25	190	115	220	240
FA40	300	150	310	340
FA50	350	165	375	390

* Refers to dimension with lid open

Features & Benefits

- Accuracy of $\pm 1\%$ of reading with a repeatability of $\pm 0.2\%$.
- Flanges drilled to BS4504 PN16.
- Durable tamper resistant construction.

Pressure & Temperature

Pressure range:-

Up to 16 bar.

Temperature Range:-

Up to 130°C.

SPECIFICATIONS	DN	15	20	25	40	50
MAX CONTINUOUS FLOW RATE	l/h	400	1000	2000	6000	20000
MIN CONTINUOUS FLOW RATE	l/h	10	30	75	225	750
OUTPUT PULSE	litre/pulse	1/1	1/1	1/1	10/1	10/1