


KENT (ELSTER) OIL METERS



FA

FLANGED OIL METER



Part No. FA

CAST IRON BODY WITH PN16 FLANGED CONNECTIONS

The Kent FA flanged oil meters provide an accurate, reliable and economical way of obtaining all the information a user needs to control oil usage and energy costs. The meters handle a wide range of viscosity's, for a variety of applications including checking and totalising fuel for burners, furnaces and diesel engines, recording draw off from storage tanks and recording general usage.

These meters are also available with a volt-free pulser incorporated within the register.

SIZE	A	B	C*	C* WITH PULSER
FA15	165	95	180	210
FA20	165	105	210	220
FA25	190	115	220	240
FA40	300	150	310	340
FA50	350	165	375	390

* Refers to dimension with lid open

Features & Benefits

- Accuracy of $\pm 1\%$ of reading with a repeatability of $\pm 2\%$.
- Flanges drilled to BS4504 PN16.
- Durable tamper resistant construction.

Pressure & Temperature

Pressure range:-

Up to 16 bar.

Temperature Range:-

Up to 130°C.

SPECIFICATIONS	DN	15	20	25	40	50
MAX CONTINUOUS FLOW RATE	l/h	400	1000	2000	6000	20000
MIN CONTINUOUS FLOW RATE	l/h	10	30	75	225	750
OUTPUT PULSE	litre/pulse	1/1	1/1	1/1	10/1	10/1