



GATE VALVES

IW3

BOLTED BONNET MARINE STYLE GATE VALVE



Part No. IW3

BRONZE BODY WITH FLANGED CONNECTIONS

SIZE	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250
A	133	140	156	159	171	213	232	248	305
B	225	245	300	345	460	545	595	670	780
C	100	100	150	150	205	255	255	305	395
D	150	165	184	203	229	279	305	368	432

IW3 bronze bolted cover gate valves are **LLOYDS APPROVED TO 3.1C** and are ideally suited for primary isolation duty for shipside use.

They are robustly constructed, have a non-rising stem and are fitted with open and shut indicators as standard.

Alternative face to face dimensions are available upon request.

Independent third party test and inspection by Lloyds, B.V., D.N.V., D.O.T. etc can be arranged usually within 1 to 2 working days.

Features & Benefits

- Lloyds Approved.
- Marine style with open & shut indicator.
- Supplied with full material certification.
- Inside screw non-rising stem.

Pressure & Temperature

PN16 Rated

For the working pressures and temperatures, see the flange rating table in the technical data section.

SUITABLE FOR SHIPSIDE DUTY



MATERIALS	
Body	LG2 Bronze
Wedge	LG2 Bronze
Spindle	Manganese Bronze
Bonnet	LG2 Bronze

Other Materials Available

- LG4 Bronze
- AB2 Ali-Bronze
- AB4 Ali-Bronze

**THIS PRODUCT IS HELD IN STOCK WITH FLANGES UNDRILLED TO
ENABLE US TO DRILL TO YOUR REQUIREMENTS**