



## GLOBE VALVES

# 182

### CAST IRON ANGLE PATTERN GLOBE VALVE



### Part No. 182

### CAST IRON BODY WITH FLANGED CONNECTIONS

SIZE	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250	DN300
A	100	105	115	125	145	155	178	203	229	248	311	350
B	197	200	200	238	273	295	334	400	473	527	622	760
C	127	127	127	152	152	152	190	254	254	390	390	508
D	115	140	150	165	185	200	229	280	305	368	432	460

The 182 cast iron bolted cover globe valve is ideally suited for secondary isolation duty. This valve provides a leak-tight shut off with the capability of being used partially open to regulate flow.

A further option allows this valve to be modified by ourselves to screw down non return, thus adding the feature of a check valve at a fraction of the cost.

#### Features & Benefits

- Specifications to BS 5152.
- Bronze trim.
- Bolted bonnet.
- Rising stem.
- Screw lift or SDNR pattern.

#### Pressure & Temperature

PN16 Rated

For the working pressures and temperatures, see the flange rating table in the technical data section.

#### MATERIALS

Body	Cast Iron
Bonnet	Cast Iron
Stem	Brass
Disc	Bronze
Seat	Bronze

**THIS PRODUCT IS HELD IN STOCK WITH FLANGES UNDRILLED TO  
ENABLE US TO DRILL TO YOUR REQUIREMENTS**