



GLOBE VALVES

182

CAST IRON ANGLE PATTERN GLOBE VALVE



Part No. 182

CAST IRON BODY WITH FLANGED CONNECTIONS

SIZE	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250	DN300
A	100	105	115	125	145	155	178	203	229	248	311	350
B	197	200	200	238	273	295	334	400	473	527	622	760
C	127	127	127	152	152	152	190	254	254	390	390	508
D	115	140	150	165	185	200	229	280	305	368	432	460

The 182 cast iron bolted cover globe valve is ideally suited for secondary isolation duty. This valve provides a leak-tight shut off with the capability of being used partially open to regulate flow.

A further option allows this valve to be modified by ourselves to screw down non return, thus adding the feature of a check valve at a fraction of the cost.

Features & Benefits

- Specifications to BS 5152.
- Bronze trim.
- Bolted bonnet.
- Rising stem.
- Screw lift or SDNR pattern.

Pressure & Temperature

PN16 Rated

Contact sales team for full details on working pressure and temperatures.

MATERIALS

Body	Cast Iron
Bonnet	Cast Iron
Stem	Brass
Disc	Bronze
Seat	Bronze

THIS PRODUCT IS GENERALLY HELD IN STOCK WITH FLANGES UNDRILLED TO ENABLE US TO DRILL TO YOUR REQUIREMENTS