



## GLOBE VALVES

# 281

### CAST STEEL ANGLE PATTERN GLOBE VALVE



#### Part No. 281

#### CAST STEEL BODY WITH FLANGED CONNECTIONS

SIZE	DN15/20	DN25	DN32/40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250
A	83	83	114	127	140	152	178	203	229	260	314
B	185	209	229	277	280	289	337	422	495	641	711
C	95	108	127	152	152	165	229	254	305	530	530
D	114	121	150	165	185	203	235	279	305	375	450

This robustly constructed cast steel bolted cover globe valve are supplied with Lloyds approved 3.1 material certification and are ideally suited for primary isolation duty for shipside use.

The valve provides a leak tight-tight shut off with the capability of being used partially open to regulate flow.

Independent third party test and inspection by Lloyds can be arranged usually within 1 to 2 working days, to meet Lloyds 3.2 certification.

#### Features & Benefits

- Lloyds Approved.
- Specifications to BS5160
- Marine style with open & shut indicator.
- Supplied with full material certification.
- Rising stem.
- Screw lift or SDNR pattern.

#### Pressure & Temperature

PN40 Rated

Contact sales team for full details on working pressure and temperatures.



Approved For Shiplside  
& Marine Boiler Duty

MATERIALS	
Body	Cast Steel
Bonnet	Cast Steel
Stem	Stainless Steel
Disc	Stainless Steel
Seat	Stainless Steel

**THIS PRODUCT IS GENERALLY HELD IN STOCK WITH FLANGES UNDRILLED TO  
ENABLE US TO DRILL TO YOUR REQUIREMENTS**