



GLOBE VALVES

JV5200

DIN 3202-1 SERIES F1 GLOBE VALVE



Part No. JV5200

CAST IRON BODY WITH PN16 FLANGED CONNECTIONS

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200
A	130	150	160	180	200	230	290	310	350	400	480	600
B	195	195	195	193	232	235	283	285	350	389	440	570
C	125	125	125	125	160	160	200	200	250	250	315	400

This bolted bonnet globe valve with a stainless steel valve disc is ideally suited for isolation duty, providing a leak-tight shut off with the capability of being used partially open to regulate flow.

Face to face dimensions to FTF series 1 according to DIN EN 5581 (DIN 3202-1 series F1).

Features & Benefits

- Gland sealed.
- Stainless steel disc
- Rising stem.

Pressure & Temperature

13 bar @ 200°C.
11 bar @ 250°C.
10 bar @ 300°C.

MATERIALS

Body	Cast Iron
Bonnet	Cast Iron
Stem	Stainless Steel
Disc	Stainless Steel

Other Materials Available

Nodular Iron Body
Cast Steel Body

SDNR – SCREW DOWN NON-RETURN & BELLOW SEALED PATTERNS AVAILABLE