



GLOBE VALVES

35.006

LLOYDS APPROVED SHIPSIDE/BOILER GLOBE VALVE



Part No. 35.006

STRAIGHT CAST STEEL BODY WITH PN40 FLANGED CONNECTIONS

Face to face length FTF series 1 to DIN EN 558-1 (DIN 3202-1 series F1)

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
A	130	150	160	180	200	230	290	310	350	400	480
B	185	185	205	205	230	230	270	305	355	395	450
C	120	120	140	140	160	160	180	200	225	250	400

The 35.006 straight pattern bolted bonnet cast steel globe valve with a stainless steel valve disc has been pressure tested and witnessed by Lloyds Register of Shipping (LRS) and therefore ideally suited for shipside and marine boiler duty. Also suitable for many other applications where isolation of steam, gases and liquids is required.

Face to face dimensions to FTF series 1 according to DIN EN 558-1 (DIN 3202-1 series F1).

Features & Benefits

- Lloyds Register of Shipping (LRS) approved.
- Supplied with 3.2 certification.
- Flanged to B.S. 4504 P.N. 40
- Gland sealed.
- Stainless steel disc.
- Rising stem.

Pressure & Temperature

- 40 bar @ 120°C.
- 35 bar @ 200°C.
- 32 bar @ 250°C.
- 28 bar @ 300°C.
- 24 bar @ 350°C.
- 21 bar @ 400°C.
- 18 bar @ 450°C.

MATERIALS

Body	Cast Steel
Bonnet	Cast Steel
Stem	Stainless Steel
Disc	Stainless Steel
Packing Ring & Gasket	Graphite



Approved For Shipline
& Marine Boiler Duty