



GLOBE VALVES

35.007

LLOYDS APPROVED SHIPSIDE/BOILER GLOBE VALVE



Part No. 35.007

ANGLED CAST STEEL BODY WITH PN40 FLANGED CONNECTIONS

Face to face length CTF series 8 to DIN EN 558-1 (DIN 3202-1 series F32)

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
A	90	95	100	105	115	125	145	155	175	200	225
B	185	185	200	200	215	215	245	280	320	360	415
C	120	120	140	140	160	160	180	200	225	250	400

The 35.007 angled pattern bolted bonnet cast steel globe valve with a stainless steel valve disc has been pressure tested and witnessed by Lloyds Register of Shipping (LRS) and therefore ideally suited for shipside and marine boiler duty. Also suitable for many other applications where isolation of steam, gases and liquids is required.

Face to face dimensions to CTF series 8 according to DIN EN 558-1 (DIN 3202-1 series F32).

Features & Benefits

- Lloyds Register of Shipping (LRS) approved.
- Supplied with 3.2 certification.
- Flanged to B.S. 4504 P.N. 40
- Gland sealed.
- Stainless steel disc.
- Rising stem.

Pressure & Temperature

- 40 bar @ 120°C.
- 35 bar @ 200°C.
- 32 bar @ 250°C.
- 28 bar @ 300°C.
- 24 bar @ 350°C.
- 21 bar @ 400°C.
- 18 bar @ 450°C.

MATERIALS

Body	Cast Steel
Bonnet	Cast Steel
Stem	Stainless Steel
Disc	Stainless Steel
Packing Ring & Gasket	Graphite



Approved For Shiplside
& Marine Boiler Duty