



BALL VALVES

BV925

PN16 FLANGED STAINLESS STEEL BALL VALVE



Part No. BV925

FULL BORE TO DIN 3202 F4, EN 558-1-27 STANDARD

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
A	115	120	125	130	140	150	170	180	190
B	80	80	90	102	110	120	140	150	180
C	130	130	165	165	205	205	300	340	420
D	95	105	115	140	150	165	185	200	220

The BV925 stainless steel bodied full bore, two piece ball valves flanged and drilled to PN16 are suited for various applications. They have a face to face to DIN 3202 F4, EN 558-1-27 standards.

These valves may be locked in the open or closed position. Blow-out proof stem prevent stem from blowing out, for maximum safety.

Fire-safe design compliance with API 607 available on request.

Features & Benefits

- ISO 5211 Top mounting pad.
- Blow-out proof stem.
- Suitable for various duties.
- Lockable in the open & closed position.
- Split body design.
- Full bore.
- Lever operated as standard.

Pressure & Temperature

PN16 Rated

Contact sales team for full details on working pressure and temperatures.

MATERIALS	
Body	CF8M
Ball & Stem	SS 316
Seats	R.P.T.F.E.
Lever	SS 304

**THESE VALVES CAN BE SUPPLIED WITH ELECTRIC
PNEUMATIC OR HYDRAULIC OPERATED ACTUATORS**