



BALL VALVES

BV925

PN16 FLANGED STAINLESS STEEL BALL VALVE



Part No. BV925

FULL BORE TO DIN STANDARD

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
A	115	120	125	130	140	150	170	180	190
B	85	86	92	103	108	125	147	161	186
C	125	125	145	195	195	250	305	305	340
D	95	105	115	140	150	165	185	200	220

The BV925 stainless steel bodied full bore, two piece ball valves flanged and drilled to PN16 are suited for various applications. They have a face to face to DIN standards.

These valves may be locked in the open or closed position.

Features & Benefits

- ISO 5211 Top mounting pad.
- Blow-out proof stem.
- Suitable for various duties.
- Lockable in the open & closed position.
- Split body design.
- Full bore.
- Lever operated.

Pressure & Temperature

PN16 Rated

For the working pressures and temperatures, see the flange rating table in the technical data section.

MATERIALS

Body & Ball	DIN 17445 1.4408/CF8M
Seats	Reinforced P.T.F.E.
Lever	AISI 304

**THESE VALVES CAN BE SUPPLIED WITH ELECTRIC
PNEUMATIC OR HYDRAULIC OPERATED ACTUATORS**