



BALL VALVES

BV927

ANSI 150 FLANGED STAINLESS STEEL BALL VALVE



Part No. BV927

FULL BORE TO ANSI 150 STANDARD

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
A	108	117	127	140	165	178	191	203	229
B	80	80	90	102	110	120	140	150	180
C	130	130	165	165	205	205	300	340	420
D	89	98	108	117	127	152	178	190	229

The BV925 stainless steel bodied full bore, two piece ball valves flanged and drilled to PN16 are suited for various applications. They have a face to face to ANSI 150 standards.

These valves may be locked in the open or closed position. Blow-out proof stem prevent stem from blowing out, for maximum safety.

Fire-safe design compliance with API 607 available on request.

Features & Benefits

- ISO 5211 Top mounting pad.
- Blow-out proof stem.
- Suitable for various duties.
- Lockable in the open & closed position.
- Split body design.
- Full bore.
- Lever operated as standard.

Pressure & Temperature

Class 150 Rated

Contact sales team for full details on working pressure and temperatures.

MATERIALS	
Body	CF8M
Ball & Stem	SS 316
Seats	R.P.T.F.E.
Lever	SS 304

**THESE VALVES CAN BE SUPPLIED WITH ELECTRIC
PNEUMATIC OR HYDRAULIC OPERATED ACTUATORS**