



BALL VALVES

BV927

ANSI 150 FLANGED STAINLESS STEEL BALL VALVE



Part No. BV927

FULL BORE WITH API 607 FIRE SAFE DESIGN

SIZE	DN15	DN20	DN25	DN40	DN50	DN65	DN80	DN100
A	108	117	127	165	178	191	203	229
B	80	83	97	111	118	144	154	174
C	130	130	160	230	230	400	400	460
D	88.9	98.6	108	127	152.4	177.8	190.5	228.6

The BV927 stainless steel bodied full bore, two piece ball valves flanged and drilled to ANSI 150 are suited for various applications. They have a API 607 fire safe design.

These valves may be locked in the open or closed position.

Features & Benefits

- ISO 5211 Top mounting pad.
- Blow-out proof stem.
- Suitable for various duties.
- Lockable in the open & closed position.
- Split body design.
- Full bore.
- Lever operated.

Pressure & Temperature

Class 150 Rated

For the working pressures and temperatures, see the flange rating table in the technical data section.

MATERIALS

Body & Ball	DIN 17445 1.4408/CF8M
Seats	Reinforced P.T.F.E.
Lever	AISI 304

**THESE VALVES CAN BE SUPPLIED WITH ELECTRIC
PNEUMATIC OR HYDRAULIC OPERATED ACTUATORS**