

IN STOCK AT
JOHNSON VALVES

SEALANTS



Boss White

Non toxic pipe jointing compound
For use on non potable hot and cold water, natural gas and low pressure steam up to 7bar and 200 deg c
Complies to BS6956 part 5 : 1992

Part No
BW400G



Boss Green

Pipe jointing compound with PTFE
For use on hot and cold water up to 7bar and 200deg c
Independently tested on air and oil to 21bar and steam to 14bar
Complies to BS6956 part 5 : 1992

Part No
BG400G



Boss Gastite

Gas jointing compound
Recommended for use with town or natural gas
Temperature resistance: -40deg c to +150deg c
Complies to BS6956 part 5 and 6a

Part No
BGT400G



PLASTICOL X10G

Gas jointing compound
Recommended for use with town or natural gas
Temperature resistance: -40deg c to +150deg c
Complies to BS6956 part 5 : 1992

Part No
PLASTICOL



Stag Type A

Non setting jointing paste for use on small joints
Resistant to gas, steam, water, petrol oil & mineral acids.
Lead Free
Complies to BS6956 part 5 : 1992

Part No
STAG



Betalube

Anti seize assembly compound
Temperature range : sub zero to 1100deg c
Recommended for use in the assembly of compression fittings

Part No
BETALUBE



PTFE

Wrc approved product
Complies with BS7786
12mm wide x 12metres

Part No
PTFE



PTFE-GAS

Gas thread sealing tape
Suitable for natural gas & LPG
Complies with BS6974
12mm wide x 12metres

Part No
PTFE-GAS