



ABS & uPVC VALVES

BFY RANGE

uPVC WAFER BUTTERFLY VALVE



Part No. BFY-50P (uPVC BODY WITH EPDM SEALS)
Part No. BFY-53P (uPVC BODY WITH FPM-VITON SEALS)
WAFER PATTERN BUTTERFLY VALVE

The BFY wafer pattern butterfly valve is designed to be sandwiched between flanges. These valves offer quick opening and closing with full flow in either direction and a leak tight shut off.

uPVC is lightweight and has excellent resistance to chemicals and abrasion, is tasteless and odourless making it ideal for use with potable water systems and most food products. uPVC is resistant to most solutions of acids, alkalis, salts and solvents which can be mixed with water.

Features & Benefits

- WRAS Approved.
- uPVC Approved to BS4346 part 1.
- Lightweight.
- Full bore.
- Materials suitable for a wide range of applications.
- Lever operated

Pressure & Temperature

Pressure range:-
2" - 5"
Up to 10 bar
6" - 10"
Up to 5 bar

Temperature Range:-
0°C to 60°C.

SIZE	2	2 1/2	3	4	5	6	8	10
A	210	210	210	210	210	299	299	450
B	223	240	255	296	311	345	408	509
C	107	127	135	154	154	174	215	248
D	50	65	80	100	125	150	200	250
E	68	65	72	95	110	123	145	210
F	43	55	55.5	53.5	63	71	78	92