



## JV060014

**Ductile Iron  
Marine Duty  
PN16 Rated  
Gate Valve**

**Flanged PN16/10**

Other flange drillings or undrilled on request



Good quality inside screw, non rising stem, non rising handwheel. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

### Approvals, Features & Benefits

- Classification society survey can be arranged
- Face to face to EN 558 Series 14 (DIN 3202 F4)
- 3.1 & 3.2 certificates available on request
- Specifications to DIN 3352 T2
- Marine style with open & shut indicator
- Bolted bonnet
- Inside screw non-rising stem.

### Pressure & Temperature

Maximum pressure:-  
DN40-DN150 : PN16 rated  
DN175-DN300 : PN10 rated

Temperature range:-  
-10°C to 120°C

SIZE*	DN40	DN50	DN65	DN80	DN100
L	140	150	170	180	190
H	270	270	295	325	360
Flange PCD	110	125	145	160	180
Flange Bolts	4 x M16	4 x M16	4 x M16	8 x M16	8 x M16
Weight Kg	11	13	17	20	28

SIZE*	DN125	DN150	DN175	DN200	DN250	DN300
L	200	210	220	230	250	270
H	450	500	560	620	730	845
Flange PCD	210	240	270	295	350	400
Flange Bolts	8 x M16	8 x M20	8 x M20	8 x M20	12 x M20	12 x M20
Weight Kg	40	50	65	85	135	180

\* Other flange drillings and sizes available on request

STANDARD MATERIALS		OPTIONAL MATERIALS (Others available on request)	
Body	Ductile Iron (GGG40)		
Trim	Bronze (LG2)	Stainless Steel	
Stem	Bronze / Special Brass (SoMs 59)	Stainless Steel	
Bonnet	Ductile Iron (GGG40)		

Do you require class approved valves? Contact sales for availability.

