



JV060025

**Bronze
Marine Gate Valve**

**Face x Face Dimensions
to ANSI B16.10**

Flanged ASA 150
Flat face as standard

(Raised face on request)

Other flange drillings or undrilled on request



Non rising stem, metal seated gate valves. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- Length to ANSI B16.10
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Marine style with open & shut indicator
- Inside screw with non-rising stem

Pressure & Temperature

*16 Bar @ 120°C

*10 Bar @ 180°C

*ANSI 150 Ratings available on request

SIZE	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
A	127	140	165	178	190	203	229	254	267
B	170	185	280	280	330	360	410	450	530
C	120	120	120	120	160	160	200	200	200
D	108.0	117.5	127.0	152.4	177.8	190.5	228.6	254.0	279.4
Weight Kg	6	8	11	12	17	25	37	55	72

STANDARD MATERIALS	OPTIONAL MATERIALS (Others available on request)	
Body	Bronze (LG2)	Bronze (LG4), Ali-Bronze (AB2, AB4)
Disc	Bronze (LG2)	Bronze (LG4), Ali-Bronze (AB2, AB4)
Stem	Manganese Bronze	
Bonnet	Bronze (LG2)	Bronze (LG4), Ali-Bronze (AB2, AB4)

Do you require class approved valves? Contact sales for availability.

