



JV060039

**Stainless Steel
ANSI 150
Non-Rising Stem
Gate Valve
Flanged ANSI 150**



The JV060039 is a stainless steel, full bore, non-rising stem gate valve with a stainless seat, wedge and stem ideally suited for water distribution, gas oil, steam petrochemical, petroleum industry and various other duties.

Features, Benefits & Approvals

- Class 150 rated
- Non-rising stem
- Bolted bonnet
- Handwheel operated
- Robust construction

Pressure & Temperature

Maximum pressure:-
19.6 Bar

Temperature range*:-
-20°C to 220°C

* Dependent on pressure

DN	15	20	25	40	50	65	80	100	150
L	108	117	127	165	178	190	203	229	267
H (opened)	182	164	198.5	248.5	278.5	312.5	377.5	429	589
W	120	120	120	200	200	200	250	250	300
d	15	20	25	40	50	65	80	100	150
G	35	43	51	73	92	105	127	157	216
D	89	98	108	127	152	178	190	229	279
C (PCD)	60.5	70	79.5	98.5	120.5	139.5	152.5	190.5	241.5
Flange Bolts	4 x M13	4 x M13	4 x M16	4 x M16	4 x M16	4 x M16	4 x M16	4 x M16	4 x M19
Kv (m³/h)	22.3	42.8	68.6	257.1	308.5	539.8	985.4	1842.3	3556.1
Weight Kg	3.05	3.61	4.78	8.05	11.16	15.67	21.51	33.09	53.45

MATERIALS

Body & Bonnet	Stainless Steel (CFM8)
Seat	Stainless Steel (CFM8)
Wedge	Stainless Steel (CFM8)
Stem	Stainless Steel (316)
Packing	PTFE
Handwheel	Iron