



**F7367**  
**Bronze**  
**JIS Marine**  
**Gate Valve**  
**Flanged JIS-5K**



Non rising stem, metal seated gate valve to JIS Japanese specifications, suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

**Features, Benefits & Approvals**

- JIS 5K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Union bonnet
- Inside screw with non-rising stem

**Pressure & Temperature**

**Non-shock water:**

7 Bar @ 120°C

**Oil & Pulsating Water:**

5 Bar

**Saturated Steam:**

2 Bar

SIZE	15	20	25	32	40	50
L	90	100	110	130	140	200
H	175	200	220	250	290	300
D2	80	100	125	125	140	
d	15	20	25	32	40	50
D	80	85	95	115	120	155
PCD	60	65	75	90	95	105
Holes	4 x 12	4 x 12	4 x 12	4 x 15	4 x 15	4 x 15
Weight Kg	2.29	2.98	4.10	5.79	7.78	

**MATERIALS**

Body	Bronze
Bonnet	Bronze
Stem	Brass
Disc	Bronze

Do you require class approved valves? Contact sales for availability.

