



## F7368

**Bronze** JIS Marine **Gate Valve** Flanged JIS-10K



Non rising stem, metal seated gate valve to Features, Benefits & Approvals JIS Japanese specifications, suitable for cold and hot water, seawater, saturated steam, oil • and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

- JIS 10K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Union bonnet
- Inside screw with non-rising stem

## **Pressure & Temperature**

Non-shock water:

14 Bar @ 120°C

Oil & Pulsating Water:

10 Bar

**Saturated Steam:** 

2 Bar

SIZE	15	20	25	32	40	50
L	100	110	120	140	150	200
Н	175	200	220	250	290	300
D2	80	100	125	125	140	
d	15	20	25	32	40	50
D	80	85	95	115	120	155
PCD	70	75	90	100	105	120
Holes	4 x M14	4 x M14	4 x M18	4 x M18	4 x M18	4 x M18
Weight Kg	2.96	3.89	5.82	7.52	9.71	

MATERIALS		
Body	Bronze	
Bonnet	Bronze	
Stem	Brass	
Disc	Bronze	

Do you require class approved valves? Contact sales for availability.











