



F7366

Cast Steel JIS Marine Gate Valve Flanged JIS-10K



Non rising stem, metal seated gate valve to Features, Benefits & Approvals JIS Japanese specifications, suitable for cold and hot water, seawater, saturated steam, oil • and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

- JIS 10K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- **Bolted bonnet**
- Inside screw with non-rising stem
- Open & shut indicator

Pressure & Temperature

Non-shock water:

14 Bar @ 120°C

Oil & Pulsating Water:

10 Bar

Saturated Steam:

2 Bar

SIZE	50	65	80	100	125	150	200	250	300	350	400
L	200	220	230	250	270	290	310	340	380	420	480
Н	300	350	400	450	520	580	700	840	960	1050	1150
D2	140	160	180	200	224	250	315	400	450	500	650
d	50	65	80	100	125	150	200	250	300	335	380
D	155	175	185	210	250	280	330	400	445	490	560
PCD	120	140	150	175	210	240	290	355	400	445	510
Bolts	4 x M18	4 x M18	8 x M18	8 x M18	8 x M22	8 x M22	12 x M22	12 x M24	16 x M24	16 x M24	16 x M26
Weight Kg	17.1	26.5	31.5	44.9	63.2	82.3	130	203	291	368	507

MATERIALS	
Body	Cast Steel
Bonnet	Cast Steel
Stem	Brass / Stainless Steel
Body Seat & Disc Ring	Bronze / Stainless Steel

Do you require class approved valves? Contact sales for availability.











