



JV061005
Bronze
Marine Gate Valve
Secured Screwed Bonnet
Flanged
PN16

Other flange drillings or undrilled on request



A marine gate valve with secured screwed bonnet, a non rising stem and a metal seat suitable for cold and hot water, seawater, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Marine style with secured screwed bonnet
- Inside screw with non-rising stem

Pressure & Temperature

Maximum pressure:-
16 bar
Temperature range:-
0°C to 120°C

DN	15	20	25	32	40	50	65	80	100
L	60	75	80	90	100	110	130	150	160
H	85	100	115	130	150	180	215	250	315
d	60	60	80	80	80	100	140	160	160
D	95	105	115	140	150	165	185	200	220
Weight Kg	1.4	1.8	2.3	3.6	4.6	6.4	9.4	12.0	19.0

STANDARD MATERIALS		OPTIONAL MATERIALS (Others available on request)	
Body	Bronze (LG2)		
Wedge	Bronze (LG2)		
Stem	Brass (SoMs59)	Bronze (CuSn6)	
Bonnet	Bronze (LG2)		

Do you require class approved valves? Contact sales for availability.

