



133
Bronze
PN16
Marine
Globe Valve
Flanged PN16
Flat Faced

Other flange drillings or undrilled on request



Suitable for cold and hot water, seawater, wet and saturated steam, oil and other neutral non aggressive liquids.

The valve provides a leak tight shut off with the capability of being used partially open to regulate flow.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Bolted cover, screw lift, rising stem
- Outside screw & yoke
- Marine style with open & shut indicator
- Screw lift or SDNR pattern

Pressure & Temperature

PN16 rated

Contact us for full details on working pressure and temperatures

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
A	108	117	127	146	159	191	216	254	305	330	356
B	95	105	115	140	150	165	185	200	220	280	
C (Open)	200	205	210	235	245	250	295	320	370	340	
D	125	125	125	125	160	160	200	200	250		
Weight Kg	4.0	4.5	6.0	10.5	9.5	13.5	20	25	40	61	

STANDARD MATERIALS	
Body & Bonnet	Bronze (RG5)
Body Seat	Bronze (RG5)
Stem	CuZn35Ni
Wedge	Bronze (RG5)

Do you require class approved valves? Contact sales for availability.

