



35.006
Cast Steel Body
Stainless Steel Disc
Globe Valve
Flanged PN40



This bolted bonnet globe valve with a stainless steel valve disc is ideally suited for isolation duty, providing a leak tight shut off with the capability of being used partially open to regulate flow.

Face to face dimensions to FTF series 1 according to DIN EN 5581 (DIN 3202-1 series F1).

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- DIN 3202-1 Series F1
- Screw lift
- Bolted bonnet
- Gland sealed
- Stainless steel disc
- Rising stem

Pressure & Temperature

PN40 rated

- 40 bar @ 120°C
- 35 bar @ 200°C
- 32 bar @ 250°C
- 28 bar @ 300°C
- 24 bar @ 350°C
- 21 bar @ 400°C
- 18 bar @ 450°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
A	130	150	160	180	200	230	290	310	350
B (Open)	194	194	218	218	251	249	298	337	391
Weight Kg	4.8	5.4	7.1	8.0	11.5	13.5	23.5	28.0	39.5

SIZE	DN125	DN150	DN200	DN250	DN300	DN350	DN400	DN500
A	400	480	600	730	850	980	1100	1350*
B (Open)	447	506	643	765	880	976	991	1176
Weight Kg	61.0	84.0	170	283	414	557	857	1150

* Length not to (DIN EN 5581) DIN 3202-1 series F1

MATERIALS	
Body	Cast Steel
Bonnet	Cast Steel
Stem & Disc	Stainless Steel
Packing Ring & Gasket	Graphite

Do you require class approved valves? Contact sales for availability.

