



35.007

**Cast Steel Body
Stainless Steel Disc
Series F32
Angled Globe Valve
Flanged PN40**



This bolted bonnet globe valve with a stainless steel valve disc is ideally suited for isolation duty, providing a leak tight shut off with the capability of being used partially open to regulate flow.

Face to face dimensions to CTF series 8 according to DIN EN 558-1 (DIN 3202-1 series F32).

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- DIN 3202-1 Series F32
- Screw Lift
- Bolted bonnet
- Gland sealed
- Stainless steel disc

Pressure & Temperature

PN40 rated

40 bar @ 120°C
35 bar @ 200°C
32 bar @ 250°C
28 bar @ 300°C
24 bar @ 350°C
21 bar @ 400°C
18 bar @ 450°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100
A	90	95	100	105	115	125	145	155	175
B (Open)	194	194	213	213	236	234	273	312	356
Weight Kg	5.2	7.2	7.4	8.4	12.4	13.6	20	25	34

SIZE	DN125	DN150	DN200	DN250	DN300	DN350	DN400	DN500
A	200	225	275	325	375	425	475	525
B (Open)	412	471	568	655	765	851	866	1021
Weight Kg	53	70	148	188	327	430	767	1018

* Centre to face not to (DIN EN 558-1) DIN 3202-1 series F32

MATERIALS	
Body	Cast Steel
Bonnet	Cast Steel
Stem & Disc	Stainless Steel
Packing Ring & Gasket	Graphite

Do you require class approved valves? Contact sales for availability.

