



JV070044

**Bronze
Union Bonnet
Screw Down Non Return
Angled
Marine
Globe Valve
Flanged PN16**

Other flange drillings or undrilled on request



Bronze secured union bonnet, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

The valve provides a leak tight shut off with a non-return design, preventing reverse flow when in the open position.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw Down Non Return (SDNR)
- Metal seated
- Rising stem
- Secured union bonnet

Pressure & Temperature

- 16 Bar @ 120°C
- 10 Bar @ 180°C

SIZE	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80
A	90	95	105	115	140	150	165	185	200
H1 (Open)	86	86	100	105	120	135	150	210	230
L1	65	65	70	75	90	100	105	115	125
Flange	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16
Weight Kg	1.4	1.8	2.1	2.6	4.2	5.2	7.5	11	14.5

STANDARD MATERIALS		OPTIONAL MATERIALS	
Body	Bronze (LG2)	Low Zinc (RG10), Zinc Free (GBZ10)	
Bonnet	Bronze (LG2)	Low Zinc (RG10), Zinc Free (GBZ10)	
Stem	Brass (SoMs59)	Bronze (CuSn6)	
Disc	Bronze (LG2)	Low Zinc (RG10), Zinc Free (GBZ10)	

Do you require class approved valves? Contact sales for availability.

