



JV070047

**Cast Iron Body
Stainless Steel Disc
Bellow Seal Type
Angled
Globe Valve
Flanged PN16**

Other flange drillings or undrilled on request



This bolted bonnet bellow sealed globe valve with a stainless steel valve disc is ideally suited for isolation duty, providing a leak tight shut off with the capability of being used partially open to regulate flow.

Face to face dimensions to CTF series 8 according to DIN EN 5581 (DIN 3202-1 series F32).

Features, Benefits & Approvals

- DIN 3202-1 Series F32
- Bellow seal type
- Gland sealed
- Stainless steel disc
- Rising stem

Pressure & Temperature

PN16 rated
16.0 bar @ 120°C
14.4 bar @ 150°C
12.8 bar @ 200°C
11.2 bar @ 250°C
9.6 bar @ 300°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250	DN300
A	90	95	100	105	115	125	145	155	175	200	225	275	325	375
B (Open)	190	190	195	195	210	210	220	235	325	345	370	485	615	665
C	125	125	125	125	150	150	175	175	300	300	400	520	520	520
Weight Kg	3.7	4.4	5.1	6.5	8.3	11.2	14.6	19.4	29.4	44	58	145	221	298

MATERIALS

Body	Cast Iron
Bonnet	Cast Iron
Stem	Stainless Steel
Disc	Stainless Steel
Bellow	Stainless Steel