



JV070052
Ductile Iron Body
Stainless Steel Disc
Screw Down Non Return
Globe Valve
Flanged PN16/10

Other flange drillings or undrilled on request



This bolted bonnet globe valve has a stainless steel valve disc with a non-return design, preventing reverse flow when in the open position. Also suitable for isolation duty, providing a leak tight shut off.

Face to face dimensions to FTF series 1 according to DIN EN 5581 (DIN 3202-1 series F1).

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- DIN 3202-1 Series F1
- Screw Down Non Return (SDNR)
- Bolted bonnet
- Gland sealed
- Stainless steel disc
- Rising stem

Pressure & Temperature

PN16 rated
16.0 bar @ 120°C
15.0 bar @ 200°C
14.0 bar @ 250°C
13.0 bar @ 300°C
11.0 bar @ 350°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250	DN300
A	130	150	160	180	200	230	290	310	350	400	480	600	730	850
B (Open)	172	172.5	182	200	255	273	295	332	369	432	483	606	758	830
Flange	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN16	PN10	PN10	PN10
Weight Kg	3.3	3.9	5.0	6.6	8.4	12.0	17.3	22.7	35.8	52.8	74.2	126	200	315

MATERIALS	
Body	Ductile Iron
Bonnet	Ductile Iron
Stem	Stainless Steel
Disc	Stainless Steel