



JV070059
Cast Steel Body
Stainless Steel Disc
Globe Valve
Flanged PN40
PN16 Flanged on request



This bolted bonnet globe valve with a stainless steel valve disc is ideally suited for isolation duty, providing a leak tight shut off with the capability of being used partially open to regulate flow.

Face to face dimensions to FTF series 1 according to DIN EN 5581 (DIN 3202-1 series F1).

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- DIN 3202-1 Series F1
- Screw lift
- Bolted bonnet
- Gland sealed
- Stainless steel disc
- Rising stem

Pressure & Temperature

Pressure range:-
PN40 rated**

Temperature range:-
-10°C to 300°C***

** PN16 rated for PN16 flange option
*** Higher temperature on request

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125
A	130	150	160	180	200	230	290	310	350	400
B	165	165	175	180	220	230	245	295	330	365
Flange	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40
Weight Kg	4	4.5	5	7	11	13	19	25	35	58

SIZE	DN150	DN175	DN200	DN250	DN300	DN350	DN400	DN450	DN500	DN600
A	480	550	600	730	850	980	1100	1200	1250	1450
B	420	500	510	600	670	755	835	920	970	1200
Flange	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40
Weight Kg	80	125	145	230	330	440	605	750	900	1130

MATERIALS

Body	Cast Steel
Bonnet	Cast Steel
Stem	Stainless Steel
Disc	Stainless Steel