



JV070062
Cast Steel Body
Stainless Steel Disc
Screw Down Non Return
Angled
Globe Valve
Flanged PN40

PN16 Flanged on request



This bolted bonnet globe valve has a stainless steel valve disc with a non-return design, preventing reverse flow when in the open position. Also suitable for isolation duty, providing a leak tight shut off.

Face to face dimensions to CTF series 8 according to DIN EN 5581 (DIN 3202-1 series F32).

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- DIN 3202-1 Series F32
- Screw Down Non Return (SDNR)
- Bolted bonnet
- Gland sealed
- Stainless steel disc
- Rising stem

Pressure & Temperature

Pressure range:-
PN40 rated**

Temperature range:-
-10°C to 300°C***

** PN16 rated for PN16 flange option
*** Higher temperature on request

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125
A	90	95	100	105	115	125	145	155	175	200
B	155	155	160	170	210	210	225	260	305	310
Flange	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40
Weight Kg	3.8	4	5	7	10	12	17	23	33	50

SIZE	DN150	DN175	DN200	DN250	DN300	DN350	DN400	DN450	DN500	DN600
A	225	250	275	325	375	425	475	500	525	550
B	350	420	420	485	530	610	660	700	765	810
Flange	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40	PN40
Weight Kg	70	90	110	155	215	275	360	395	485	650

MATERIALS	
Body	Cast Steel
Bonnet	Cast Steel
Stem	Stainless Steel
Disc	Stainless Steel