



**F7351**  
**Bronze Body**  
**Bronze/Brass Disc**  
**Screw Down Non Return**  
**JIS Marine**  
**Globe Valve**  
**Flanged JIS-5K**



Bronze metal seated gland packed globe valve to JIS Japanese specifications. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

This valve has a non-return design, preventing reverse flow when in the open position. Also suitable for isolation duty, providing a leak tight shut off.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

**Features, Benefits & Approvals**

- JIS 5K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw Down Non Return (SDNR)
- 15-40mm Secured screwed bonnet
- 50-65mm Bolted bonnet
- Gland sealed
- Bronze / brass disc
- Rising stem

**Pressure & Temperature**

**Non-shock water:**

7 Bar @ 120°C

**Air, Gas, Steam, Pulsating Water:**

5 Bar @ 205°C

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65
L	100	110	120	140	160	210	250
H	130	140	160	170	190	235	260
A	80	85	95	115	120	130	155
PCD	60	65	75	90	95	105	130
Holes	4 x 12	4 x 12	4 x 12	4 x 15	4 x 15	4 x 15	4 x 15
Weight Kg	2.02	2.86	3.54	5	6.48	11.7	17

**MATERIALS**

Body	Bronze
Bonnet	Bronze / Brass
Stem	Brass
Disc	Bronze / Brass

Do you require class approved valves? Contact sales for availability.

