



F7409
Bronze Body
Bronze/Brass Disc
Screw Down Non Return
JIS Marine
Globe Valve
Flanged JIS-16K



Bronze metal seated gland packed globe valve to JIS Japanese specifications. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

This valve has a non-return design, preventing reverse flow when in the open position. Also suitable for isolation duty, providing a leak tight shut off.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- JIS 16K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw Down Non Return (SDNR)
- Secured screwed bonnet
- Gland sealed
- Bronze / brass disc
- Rising stem

Pressure & Temperature

Non-shock water:

22 Bar @ 120°C

Air, Gas, Steam, Pulsating Water:

16 Bar @ 205°C

| SIZE | DN15 | DN20 | DN25 | DN32 | DN40 |
|-----------|--------|--------|--------|--------|--------|
| L | 110 | 120 | 130 | 160 | 180 |
| H | 130 | 140 | 160 | 170 | 190 |
| A | 95 | 100 | 125 | 135 | 140 |
| PCD | 70 | 75 | 90 | 100 | 105 |
| Holes | 4 x 15 | 4 x 15 | 4 x 19 | 4 x 15 | 4 x 19 |
| Weight Kg | 2.76 | 3.72 | 5.20 | 6.91 | 8.43 |

| MATERIALS | |
|-----------|----------------|
| Body | Bronze |
| Bonnet | Bronze / Brass |
| Stem | Brass |
| Disc | Bronze / Brass |

Do you require class approved valves? Contact sales for availability.

