


Globe Valves



Bronze metal seated gland packed globe valve to JIS Japanese specifications.

Suitable for cold and hot water, seawater,

saturated steam, oil and other neutral

Independent third party test and

inspection by various classification

society surveyor's can be arranged for

shipside and primary isolation duties.

non aggressive liquids.

F7304

Bronze Body Bronze/Brass Disc Angled JIS Marine Globe Valve Flanged JIS-16K

Features, Benefits & Approvals

- JIS 16K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw lift
- 15-40mm Secured screwed bonnet
- 50-65mm Bolted bonnet
- Gland sealed
- Bronze / brass disc
- Rising stem

Pressure & Temperature

Non-shock water: 22 Bar @ 120°C

Air, Gas, Steam, Pulsating Water: 16 Bar @ 205°C

SIZE	DN15	DN20	DN25	DN32	DN40
L1	70	75	85	95	100
H1	120	130	145	150	165
А	95	100	125	135	140
PCD	70	75	90	100	105
Holes	4 x 15	4 x 15	4 x 19	4 x 15	4 x 19
Weight Kg	2.73	3.65	5.16	6.72	8.13

MATERIALS	
Body	Bronze
Bonnet	Bronze / Brass
Stem	Brass
Disc	Bronze / Brass

Do you require class approved valves? Contact sales for availability.

