



## JV070078

**Bronze  
ANSI B16.10 Length  
Marine Globe Valve**

**Flanged ASA 150  
Flat Face**

(Raised face on request)



Bronze bolted cover, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

### Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Length to ANSI B16.10
- Screw lift
- Metal seated
- Rising stem
- Bolted bonnet

### Pressure & Temperature

15.5 Bar @ 60°C
14.3 Bar @ 100°C
13.4 Bar @ 125°C
12.5 Bar @ 150°C
11.5 Bar @ 175°C
10.7 Bar @ 200°C
9.6 Bar @ 225°C

Note: Steam up to 180°C only

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
<b>A</b>	108	117	127	140	165	203	216	241	292	356	406
<b>B (Open)</b>	155	160	175	180	205	215	235	275	325	365	405
<b>Flange</b>	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150
<b>Weight Kg</b>	2.1	2.6	3.5	4.5	6.7	9.2	13.0	18.0	27.0	36.0	52.0

STANDARD MATERIALS		OPTIONAL MATERIALS
<b>Body</b>	Bronze (LG2)	Al-Bronze
<b>Bonnet</b>	Bronze (LG2)	
<b>Stem</b>	Brass (SoMs59)	Bronze (CuSn6)
<b>Disc</b>	Bronze (LG2)	Al-Bronze

Do you require class approved valves? Contact sales for availability.

