



JV070079

**Bronze
Screw Down Non Return
ANSI B16.10 Length
Marine Globe Valve**

**Flanged ASA 150
Flat Face**

(Raised face on request)



Bronze bolted cover, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

The valve provides a leak tight shut off with a non-return design, preventing reverse flow when in the open position.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Length to ANSI B16.10
- Screw Down Non Return (SDNR)*
- Metal seated
- Rising stem
- Bolted bonnet

* No spring fitted but available on request if required

Pressure & Temperature

15.5 Bar @ 60°C
14.3 Bar @ 100°C
13.4 Bar @ 125°C
12.5 Bar @ 150°C
11.5 Bar @ 175°C
10.7 Bar @ 200°C
9.6 Bar @ 225°C

Note: Steam up to 180°C only

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
A	108	117	127	140	165	203	216	241	292	356	406
B (Open)	155	160	175	180	205	215	235	275	325	365	405
Flange	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150
Weight Kg	2.1	2.6	3.5	4.5	6.7	9.2	13.0	18.0	27.0	36.0	52.0

STANDARD MATERIALS		OPTIONAL MATERIALS
Body	Bronze (LG2)	Alu-Bronze
Bonnet	Bronze (LG2)	
Stem	Brass (SoMs59)	Bronze (CuSn6)
Disc	Bronze (LG2)	Alu-Bronze

Do you require class approved valves? Contact sales for availability.

