



JV070081

**Stainless Steel
PN16
Globe Valve
BSP Threaded**



The JV070081 is an economical globe valve constructed in stainless steel making it suitable for a wide range of duties.

Ideally suited for isolation duty, providing a leak-tight shut off with the capability of being used partially open to regulate flow.

Features & Benefits

- Screwed bonnet
- Rising stem
- Reduced bore
- Suitable for wide range of duties

Pressure & Temperature

Pressure range:-
PN16 Rated

Temperature range:-
-20°C to 180°C

Not for use on steam

BSP	3/8	1/2	3/4	1	1 1/4	1 1/2	2
d	12	12	15	20	25	32	40
L	52	52	60	72	81	90	101
L1	12.5	12.5	13	17.5	19	20	20
H (opened)	79	79	94	101	119	142	159
H (closed)	73	73	85	91	103	124	139
V	70	70	70	80	80	90	100
Flow Coefficient Kvs (M ³ /h)	1.28	1.88	3.06	5.67	9.05	15.18	24.94
Weight Kg	0.26	0.26	0.44	0.60	0.96	1.22	1.74

MATERIALS

Body & Bonnet	Stainless Steel (A351 CF8M)
Disc & Stem	Stainless Steel (316)
Handwheel	Steel
Packing	PTFE

Head Loss Graph

