



JV070085

Stainless Steel Globe Valve

Flanged ANSI 150

Other flange drillings on request



A stainless steel globe valve that is ideally suited for use on a wide range of duties that are compatible with materials, it provides a leak tight shut off with the capability of being used partially open to regulate flow.

Features, Benefits & Approvals

- Screw lift
- Bolted bonnet
- Gland sealed
- Rising stem

Pressure & Temperature*

Pressure range:-
Class 150 rated

Temperature range:-
-20°C to 180°C

* 5 Bar max if used for steam service

| DN | 25 | 40 | 50 | 65 | 80 | 100 |
|--------------|---------|---------|---------|---------|---------|---------|
| L | 127 | 165 | 203 | 216 | 241 | 292 |
| H | 173 | 200 | 230 | 243 | 286 | 325 |
| W | 140 | 160 | 200 | 200 | 250 | 250 |
| Flange PCD | 79.4 | 98.4 | 120.7 | 139.7 | 152.4 | 190.5 |
| Flange Bolts | 4 x M16 | 4 x M16 | 4 x M16 | 4 x M16 | 4 x M16 | 4 x M16 |
| Weight Kg | 3.9 | 7.2 | 11.3 | 21.5 | 34.2 | 62.0 |

MATERIALS

| | |
|-------------------------|------------------------|
| Body | Stainless Steel (CF8M) |
| Bonnet | Stainless Steel (CF8M) |
| Stem | Stainless Steel (316) |
| Packing Sleeve & Gasket | PTFE |
| Disc | Stainless Steel (CF8M) |
| Handwheel | Iron |