



JV070086

Bronze
ANSI B16.10 Length
Angled
Marine Globe Valve
Flanged ASA 150

Other flange drillings or undrilled on request



Bronze bolted cover, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Length to ANSI B16.10
- Screw lift
- Metal seated
- Rising stem
- Bolted bonnet

Pressure & Temperature

15.5 Bar @ 60°C
14.3 Bar @ 100°C
13.4 Bar @ 125°C
12.5 Bar @ 150°C
11.5 Bar @ 175°C
10.7 Bar @ 200°C
9.6 Bar @ 225°C

Note: Steam up to 180°C only

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
A	57	64	70	76	83	102	108	121	146	178	203
B (Open)	135	140	155	160	180	190	210	230	280	315	340
Flange	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150
Weight Kg	2.2	3.0	3.7	5.0	7.0	8.8	13.0	17.0	24.0	35.0	51.0

STANDARD MATERIALS		OPTIONAL MATERIALS	
Body	Bronze (LG2)	Ali-Bronze	
Bonnet	Bronze (LG2)		
Stem	Brass (SoMs59)	Bronze (CuSn6)	
Disc	Bronze (LG2)	Ali-Bronze	

Do you require class approved valves? Contact sales for availability.

