



F7311
Cast Steel Body
Bronze / Stainless Steel Disc
JIS Marine
Globe Valve
Flanged JIS-5K



Cast steel metal seated gland packed globe valve to JIS Japanese specifications. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- JIS 5K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw lift
- Bolted bonnet
- Gland sealed
- Rising stem

Pressure & Temperature

Non-shock water:

7 Bar @ 120°C

Air, Gas, Steam, Pulsating Water:

5 Bar @ 205°C

DN	50	65	80	100	125	150	200	250	300
L	210	250	280	340	410	480	570	740	840
H (open)	270	300	310	360	390	445	530	795	930
W	160	180	180	224	250	280	315	355	400
d	50	65	80	100	125	150	200	250	300
D	130	155	180	200	235	265	320	385	430
PCD	105	130	145	165	200	230	280	345	390
Holes	4 x 15	4 x 15	4 x 19	8 x 19	8 x 19	8 x 19	8 x 23	12 x 23	12 x 23
Weight Kg	16.2	23.4	30	45	63	88	153	230	309

MATERIALS

Body	Cast Steel
Bonnet	Cast Steel
Stem	Brass / Stainless Steel
Disc & Body Seat	Bronze / Stainless Steel

Do you require class approved valves? Contact sales for availability.

