



## JV070087

**Bronze**  
**Screw Down Non Return**  
**ANSI B16.10 Length**  
**Angled**  
**Marine Globe Valve**  
**Flanged ASA 150**

Other flange drillings or undrilled on request



Bronze bolted cover, rising stem, metal seated gland packed globe valve. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

The valve provides a leak tight shut off with a non-return design, preventing reverse flow when in the open position.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

### Features, Benefits & Approvals

- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Length to ANSI B16.10
- Screw Down Non Return (SDNR)\*
- Metal seated
- Rising stem
- Bolted bonnet

\* No spring fitted but available on request if required

### Pressure & Temperature

15.5 Bar @ 60°C
14.3 Bar @ 100°C
13.4 Bar @ 125°C
12.5 Bar @ 150°C
11.5 Bar @ 175°C
10.7 Bar @ 200°C
9.6 Bar @ 225°C

**Note: Steam up to 180°C only**

SIZE	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150
<b>A</b>	57	64	70	76	83	102	108	121	146	178	203
<b>B (Open)</b>	135	140	155	160	180	190	210	230	280	315	340
<b>Flange</b>	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150	ASA 150
<b>Weight Kg</b>	2.2	3.0	3.7	5.0	7.0	8.8	13.0	17.0	24.0	35.0	51.0

STANDARD MATERIALS		OPTIONAL MATERIALS	
<b>Body</b>	Bronze (LG2)	Al-Bronze	
<b>Bonnet</b>	Bronze (LG2)		
<b>Stem</b>	Brass (SoMs59)	Bronze (CuSn6)	
<b>Disc</b>	Bronze (LG2)	Al-Bronze	

Do you require class approved valves? Contact sales for availability.

