


Globe Valves



F7314

Cast Steel Body Bronze / Stainless Steel Disc JIS Marine Angled Globe Valve Flanged JIS-20K

Features, Benefits & Approvals

- JIS 20K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw lift
- Bolted bonnet
- Gland sealed
- Rising stem

<u> </u>
200
ABA
8.5
F

Pressure & Temperature

34 bar @ 0 to 120°C 31 bar @ 220°C

globe valve to JIS Japanese specifications. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids. Independent third party test and inspection

Cast steel metal seated gland packed

by various classification society surveyor's can be arranged for shipside and primary isolation duties.

DN	50	65	80	100	125	150	200	250
L1	125	135	150	170	200	225	280	310
H (open)	275	305	340	385	440	485	540	560
w	200	224	250	280	315	365	450	560
d	50	65	80	100	125	150	200	250
D	155	175	200	225	270	305	350	380
PCD	120	140	160	185	225	260	305	380
Holes	8 x M18	8 x M18	8 x M22	8 x M22	8 x M24	8 x M24	12 x M24	12 x M26
Weight Kg	20.0	26.9	38.9	54.4	79.9	111	181	283

MATERIALS	
Body	Cast Steel
Bonnet	Cast Steel
Stem	Brass / Stainless Steel
Disc & Body Seat	Bronze / Stainless Steel

Do you require class approved valves? Contact sales for availability.

