



**F7472**  
**Cast Steel Body**  
**Bronze / Stainless Steel Disc**  
**JIS Marine**  
**Angled**  
**Screw Down Non Return**  
**Globe Valve**  
**Flanged JIS-10K**



Cast steel metal seated gland packed globe valve to JIS Japanese specifications. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

This valve has a non-return design, preventing reverse flow when in the open position. Also suitable for isolation duty, providing a leak tight shut off.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

**Features, Benefits & Approvals**

- JIS 10K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw Down Non Return (SDNR)
- Bolted bonnet
- Gland sealed
- Rising stem

**Pressure & Temperature**

14 bar @ 0 to 120°C

12 bar @ 220°C

DN	50	65	80	100	125	150	200
L1	120	130	140	160	180	205	230
H (open)	235	250	255	290	340	385	460
W	200	224	250	280	315	355	450
d	50	65	80	100	125	150	200
D	155	175	185	210	250	280	330
PCD	120	140	150	175	210	240	290
Holes	4 x M16	4 x M16	8 x M16	8 x M16	8 x M20	8 x M20	12 x M20
Weight Kg	16.3	23.0	25.3	37.0	57.1	77.2	116

**MATERIALS**

Body	Cast Steel
Bonnet	Cast Steel
Stem	Brass / Stainless Steel
Disc & Body Seat	Bronze / Stainless Steel

Do you require class approved valves? Contact sales for availability.

