



F7474

Cast Steel Body
Bronze / Stainless Steel Disc
JIS Marine
Angled
Screw Down Non Return
Globe Valve
Flanged JIS-20K



Cast steel metal seated gland packed globe valve to JIS Japanese specifications. Suitable for cold and hot water, seawater, saturated steam, oil and other neutral non aggressive liquids.

This valve has a non-return design, preventing reverse flow when in the open position. Also suitable for isolation duty, providing a leak tight shut off.

Independent third party test and inspection by various classification society surveyor's can be arranged for shipside and primary isolation duties.

Features, Benefits & Approvals

- JIS 20K specifications
- Class society survey can be arranged
- 3.1 & 3.2 certificates available on request
- Screw Down Non Return (SDNR)
- Bolted bonnet
- Gland sealed
- Rising stem

Pressure & Temperature

34 bar @ 0 to 120°C

31 bar @ 220°C

| DN | 32 | 40 | 50 | 65 | 80 | 100 | 125 | 150 | 200 | 250 |
|-----------|---------|---------|---------|---------|---------|---------|---------|---------|----------|----------|
| L1 | 100 | 110 | 125 | 135 | 150 | 170 | 200 | 225 | 280 | 310 |
| H (open) | 240 | 255 | 270 | 295 | 325 | 365 | 415 | 460 | 520 | 595 |
| W | 160 | 160 | 200 | 224 | 250 | 280 | 315 | 365 | 450 | 560 |
| d | 32 | 40 | 50 | 65 | 80 | 100 | 125 | 150 | 200 | 250 |
| D | 135 | 140 | 155 | 175 | 200 | 225 | 270 | 305 | 350 | 380 |
| PCD | 100 | 105 | 120 | 140 | 160 | 185 | 225 | 260 | 305 | 380 |
| Holes | 4 x M18 | 4 x M18 | 8 x M18 | 8 x M18 | 8 x M22 | 8 x M22 | 8 x M24 | 8 x M24 | 12 x M24 | 12 x M26 |
| Weight Kg | 15.0 | 16.0 | 20.0 | 26.9 | 38.9 | 54.4 | 79.9 | 111 | 181 | 283 |

| MATERIALS | | | | | | |
|------------------|--------------------------|--|--|--|--|--|
| Body | Cast Steel | | | | | |
| Bonnet | Cast Steel | | | | | |
| Stem | Brass / Stainless Steel | | | | | |
| Disc & Body Seat | Bronze / Stainless Steel | | | | | |

Do you require class approved valves? Contact sales for availability.











