



JV070100

**Stainless Steel
Globe Valve**

Flanged PN16

DIN Length



A stainless steel globe valve with lengths to DIN standards that is ideally suited for use on a wide range of duties that are compatible with materials, it provides a leak tight shut off with the capability of being used partially open to regulate flow.

Features, Benefits & Approvals

- Length to DIN standards
- Screw lift
- Bolted bonnet
- Gland sealed
- Rising stem

Pressure & Temperature*

Pressure range:-
PN16 rated

Temperature range:-
-20°C to 200°C

DN	15	20	25	40	50	65	80	100	150
L	130	150	160	200	230	290	310	350	480
H	178	181	200	245	258	310	325	390	531
W	140	140	140	160	200	200	250	250	350
Flange PCD	65	75	85	110	125	145	160	180	240
Flange Bolts	4 x M12	4 x M12	4 x M12	4 x M16	4 x M16	4 x M16	8 x M16	8 x M16	8 x M20
Kv (m ³ /h)	8.6	12.	17.1	34.3	47.1	85.7	107.1	171.4	385.6
Weight Kg	3.5	4.3	6.3	12.5	15	22.5	27.5	42	57

MATERIALS

Body	Stainless Steel (CF8M)
Bonnet	Stainless Steel (CF8M)
Stem	Stainless Steel (316)
Packing Sleeve & Gasket	PTFE
Disc	Stainless Steel (CF8M)
Handwheel	Iron