



JV120015

**Bronze
30° Oblique Pattern
Fire Hydrant
Landing Globe Valve**

**BSP, NPT or NST Male Outlet
BSP Male Inlet**



The JV120015 fire hydrant valve is suitable for both offshore and onshore applications.

This valve is manufactured with a corrosion resistant LG2 bronze body and can be painted red on request.

It is available with BSP, NPT or NST threaded connections as standard but can be supplied with a wide range of international hose connections.

Approvals, Features & Benefits

- 3.1 material certification on request
- Screwed bonnet
- BSP, NPT or NST male outlet
- Optional outlet fittings (e.g. Storz, etc.)

Pressure & Temperature

Maximum pressure:-
PN16

Temperature range:-
0°C to 80°C

DN	25	32	40	50	65	80	100
G1 / G2	1"	1¼"	1½"	2"	2½"	3"	4"
L	63	65	80	100	105	135	160
L1	18	18	20	20	22	24	24
H	145	160	190	200	240	275	310
d	60	80	80	100	120	160	160
Weight Kg	0.7	1.5	2.1	2.8	3.3	5.9	9.1

MATERIALS

Body	Bronze (LG2)
Bonnet	DN15-65 Brass, DN80-100 Bronze (LG2)
Stem	Special Brass (SoMs 59)
Seat	Special Brass (SoMs 59) & NBR Seal
Handwheel	Cast Iron



Optional International Outlets

Available in the following:-

Storz • Gost • NST
NOR • SMS • Form 63
Guillemin • Nakajima • ROTA

