



## JV121008

**Bronze  
Straight Pattern  
Marine Landing  
Fire Rated  
Diaphragm Valve**

**Storz Outlet**

**Flanged Inlet**  
PN10/16 (standard)  
BS10 D/E  
ANSI 125  
JIS 10K



Marine grade bolted bonnet landing diaphragm valve suitable for fire fighting and deck washing.

This valve is manufactured with a corrosion resistant LG2 bronze body and a FPM fire rated diaphragm.

They are available with Storz connection as standard but can be supplied with a wide range of other international connections.

### Approvals, Features & Benefits

- Lloyds Register type approved
- 3.1 material certification on request
- Bolted bonnet
- Fire rated diaphragm
- Storz outlet

### Pressure & Temperature

Maximum pressure:-  
PN10

Temperature range:-  
0°C to 286°C

DN (VALVE) DN (ADAPTOR)	50 Storz C-52	65 Storz C-52	65 Storz 65	65 Storz B-75
H	183	200	200	200
L	228	285	285	285
øC	140	140	140	140
øD	165	185	185	185
øA	66	66	81	89
øB	98	98	118	126
WEIGHT Kg	10.2	15.0	15.0	15.0

STANDARD MATERIALS		OPTIONAL MATERIALS (Others available on request)
Body & Bonnet	Bronze (LG2)	
Stem	Special Brass (SoMs 59)	Phosphor Bronze (CuSn6)
Disc	Bronze (LG2)	
Adapter & Cap	Brass (MS58)	Bronze (LG2)
Handwheel	Bronze (LG2)	Bronze (LG2)
Diaphragm	FPM	



### Optional International Outlets

Available in the following:-

Storz • Gost • NST  
NOR • SMS • Form 63  
Guillemain • Nakajima • ROTA

