

JV151005

Stainless Steel Y Type Strainer BSP Threaded



The JV151015 stainless steel Y-type strainer is ideally suited for the protection of meters, pumps, valves and other pipeline equipment in a wide range of applications including chemical & petrochemical industries.

Approvals, Features & Benefits

- 3.1 material certificate on request
- Y-type with drain plug
- Economical & efficient
- Easily removable screen for cleaning

Pressure & Temperature

Maximum pressure:-

16 bar


Temperature range:-

-50°C to 200°C

BSP	1/4"	³/ ₈ "	1/2"	3/4"	1"	1¼"	1½"	2"
L	64	64	64	80	89	106.5	118	139
L1	12	12	13	14.5	16.5	19	23	23
d	10.5	12.5	15	20	25	32	38	50
G	1/4"	1/4"	1/4"	1/4"	3/8"	1/2"	1/2"	1/2"
G1	23.8 x 1.5	23.8 x 1.5	23.8 x 1.5	29.5 x1.5	39.8 x 1.5	41.8 x 1.5	49.8 x 1.5	59.8 x 1.5
Screen Mesh Perforation	1	1	1	1	1	1	1	1
Weight Kg	0.23	0.21	0.21	0.35	0.61	0.89	1.11	1.63

MATERIALS	
Body	Stainless Steel (EN 1.4408)
Filter Screen	Stainless Steel (AISI 304)
Plug	Stainless Steel (EN 1.4408)
Gasket	PTFE

Head Loss Graph



Flow (L/Min)