



JV160002
Carbon Steel
Thermodynamic
Steam Trap
Flanged
PN40



The JV160002 thermodynamic steam trap is manufactured and tested in accordance with the DIN standards and the relevant German regulations for steam boilers (TRD) and pressure vessels (AD).

Maximum downstream pressure should not exceed 80% of upstream pressure. The trap should be installed in horizontal position only.

Approvals, Features & Benefits

- Manufactured to DIN standards
- Tested to TRD & AD regulations
- Economical & efficient
- In-built strainer
- Easily removable screen for cleaning

Pressure & Temperature

Max pressure:-
40 bar
Max temperature:-
0°C to 400°C

| DN | 15 | 20 | 25 |
|-----------|-----|-----|-----|
| L | 150 | 150 | 160 |
| D | 95 | 105 | 115 |
| b | 16 | 18 | 18 |
| k | 65 | 75 | 85 |
| g | 45 | 58 | 68 |
| i | 14 | 14 | 14 |
| Weight Kg | 3.4 | 4.1 | 4.5 |

MATERIALS

| | |
|--------------|-----------------|
| Body | Carbon Steel |
| Cover | Carbon Steel |
| Disc | Stainless Steel |
| Seat | Stainless Steel |

Discharge Capacities

