



JV190005

**Bronze
Sleeved Packed
Lever Operated
Water Tank Level Gauge
Top & Bottom Set
Flanged Undrilled**
(Drilled to your requirements on request)



The JV190005 set of gauge cocks are fitted with sleeves which can be adjusted by means of packing nuts as wear necessitates, providing easy and efficient maintenance.

Both the top and bottom fittings have sleeved packed, lever operated valves with a drain cock on the bottom fitting.

The fittings can be handed right or left to suit installation.

Approvals, Features & Benefits

- Sleeve packed for easy maintenance
- Drain cock
- Sight glass tube cut to size on request
- Tube guard protectors on request
- Spare sealing rings & sleeves available

Pressure & Temperature

Max working pressure:-
17.2 bar

Temperature range:-
260°C @ 17.2 bar

DN	15	20	20
Pattern	Standard	Standard	Lightweight
Sight Glass Tube Dia.	13	19	19
A	83	97	82
B	115	115	115
C	62	62	62
E	13	13	13
F	19	25	19
G	16	16	16
Weight Kg	5.44	8.16	5.44

MATERIALS

Body	Bronze
Spindle	Steel

Glass Sight Tube & Protectors (on request)

It is necessary to state the distance between the centres at which the gauge cocks are to be fitted when ordering.



Optional Bronze Intermediate Arm

To provide extra support for long sight tube installations.

